

ODP-2-26550-3K042-MN

Optidrive P2 VFD Datasheet

5.5 kW, 9 A, 500-600 V, 3PH

IP20 Variable Frequency Drive with TFT Display



Input Ratings

| | |
|-----------------------------|-----------|
| Supply Voltage | 500-600 V |
| Input Phases | 3 |
| Supply Current Continuous | 10.8 A |
| Supply Fuse or MCB (Type B) | 16 A |

Output Ratings

| | |
|---------------------|--------------------|
| Motor Output Rating | 5.5 kW (7.5 HP) |
| Output Voltage | 0 – Supply Voltage |
| Output Current | 9 A |

Cable Information

| | |
|------------------------|--------------------------------|
| Max Supply Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Size | 8 mm ² (0.01 sq in) |
| Max Motor Cable Length | 100 m (328 ft) |

Factory Build Options

| | |
|------------------|-----------------|
| EMC Filter | No Internal EMC |
| Brake Transistor | Internal |
| Enclosure | IP20 |
| Display | TFT Display |
| PCB Coating | Standard |



Drive Dimensions

| | |
|---------|-------------------|
| Size | 2 |
| Height | 221 mm (8.7 in) |
| Width | 110 mm (4.33 in) |
| Depth | 185 mm (7.28 in) |
| Weight | 1.8 kg (3.97 lbs) |
| Fixings | 4 x M4 |

Packaged Dimensions

| | |
|--------|-------------------|
| Height | 265 mm (10.43 in) |
| Width | 145 mm (5.71 in) |
| Depth | 230 mm (9.06 in) |
| Weight | 1.9 kg (4.19 lbs) |



Buy this drive or get more information:
<https://www.shc-gmbh.com>

