

ODP-2-32040-3KF4A-MN

Optidrive P2 VFD Datasheet

4 kW, 18 A, 200-240 V, 3PH

IP66 Non Switched Outdoor Variable Frequency Drive with EMC Filter and TFT Display



Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	21.6 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	4 kW (5 HP)
Output Voltage	0 – Supply Voltage
Output Current	18 A

Cable Information

Max Supply Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Size	8 mm ² (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP66 Non Switched Outdoor
Display	TFT Display
PCB Coating	Standard



Drive Dimensions

Size	3
Height	310 mm (12.2 in)
Width	211 mm (8.31 in)
Depth	225 mm (8.86 in)
Weight	6.6 kg (14.55 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	305 mm (12.01 in)
Width	270 mm (10.63 in)
Depth	440 mm (17.32 in)
Weight	7.6 kg (16.76 lbs)



Buy this drive or get more information:
<https://www.shc-gmbh.com>

