

ODP-2-72075-3KF4N-MN

Optidrive P2 VFD Datasheet

75 kW, 248 A, 200-240 V, 3PH

IP55 Variable Frequency Drive with EMC Filter and TFT Display



Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	255.5 A
Supply Fuse or MCB (Type B)	315 A

Output Ratings

Motor Output Rating	75 kW (100 HP)
Output Voltage	0 – Supply Voltage
Output Current	248 A

Cable Information

Max Supply Cable Size	150 mm ² (0.23 sq in)
Max Motor Cable Size	150 mm ² (0.23 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	IP55
Display	TFT Display
PCB Coating	Standard



Drive Dimensions

Size	7
Height	1280 mm (50.39 in)
Width	330 mm (12.99 in)
Depth	358 mm (14.09 in)
Weight	89 kg (196.21 lbs)
Fixings	4 x M10

Packaged Dimensions

Height	1420 mm (55.91 in)
Width	540 mm (21.26 in)
Depth	560 mm (22.05 in)
Weight	96 kg (211.64 lbs)



Buy this drive or get more information:
<https://www.shc-gmbh.com>

