

# ODP-2-84250-3KR4N-MN

## Optidrive P2 VFD Datasheet

### 250 kW, 480 A, 380-480 V, 3PH

IP55 Variable Frequency Drive with TFT Display



#### Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	480 A
Supply Fuse or MCB (Type B)	600 A

#### Output Ratings

Motor Output Rating	250 kW (400 HP)
Output Voltage	0 – Supply Voltage
Output Current	480 A

#### Cable Information

Max Supply Cable Size	240 mm <sup>2</sup> (0.37 sq in)
Max Motor Cable Size	240 mm <sup>2</sup> (0.37 sq in)
Max Motor Cable Length	100 m (328 ft)

#### Factory Build Options

EMC Filter	High Performance EMC Filter
Brake Transistor	Internal
Enclosure	IP55
Display	TFT Display
PCB Coating	Standard

#### Drive Dimensions

Size	8
Height	1334 mm (52.52 in)
Width	444 mm (17.48 in)
Depth	423 mm (16.65 in)
Weight	144 kg (317.47 lbs)
Fixings	4 x M12

#### Packaged Dimensions

Height	980 mm (38.58 in)
Width	610 mm (24.02 in)
Depth	1040 mm (40.94 in)
Weight	165 kg (363.76 lbs)



Buy this drive or get more information:  
<https://www.shc-gmbh.com>

