

# ODV-3-240095-3F1E-MN

## Optidrive Eco VFD Datasheet

### 4 kW (5 HP), 9.5 A, 380-480 V, 3PH

IP66 With Disconnect Outdoor Variable Frequency Drive with EMC Filter and TFT Display



#### Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	8.6 A
Supply Fuse or MCB (Type B)	10 A

#### Output Ratings

Motor Output Rating	4 kW (5 HP)
Output Voltage	0 – Supply Voltage
Output Current	9.5 A

#### Cable Information

Max Supply Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Size	8 mm <sup>2</sup> (0.01 sq in)
Max Motor Cable Length	100 m (328 ft)

#### Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP66 With Disconnect Outdoor
Display	TFT Display
PCB Coating	Standard

#### Drive Dimensions

Size	2
Height	257 mm (10.12 in)
Width	188 mm (7.4 in)
Depth	182 mm (7.17 in)
Weight	3.5 kg (7.72 lbs)
Fixings	4 x M4

#### Packaged Dimensions

Height	215 mm (8.46 in)
Width	235 mm (9.25 in)
Depth	375 mm (14.76 in)
Weight	4.2 kg (9.26 lbs)



Buy this drive or get more information:  
<https://www.shc-gmbh.com>

