

# ODV-3-420300-3F1N-MN

## Optidrive Eco VFD Datasheet

### 7.5 kW (10 HP), 30 A, 200-240 V, 3PH

IP55 Variable Frequency Drive with EMC Filter and TFT Display



#### Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	27 A
Supply Fuse or MCB (Type B)	32 A

#### Output Ratings

Motor Output Rating	7.5 kW (10 HP)
Output Voltage	0 – Supply Voltage
Output Current	30 A

#### Cable Information

Max Supply Cable Size	16 mm <sup>2</sup> (0.02 sq in)
Max Motor Cable Size	16 mm <sup>2</sup> (0.02 sq in)
Max Motor Cable Length	100 m (328 ft)

#### Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP55
Display	TFT Display
PCB Coating	Standard

#### Drive Dimensions

Size	4
Height	450 mm (17.72 in)
Width	171 mm (6.73 in)
Depth	252 mm (9.92 in)
Weight	11.5 kg (25.35 lbs)
Fixings	4 x M8

#### Packaged Dimensions

Height	510 mm (20.08 in)
Width	240 mm (9.45 in)
Depth	330 mm (12.99 in)
Weight	13.5 kg (29.76 lbs)



Buy this drive or get more  
information:  
<https://www.shc-gmbh.com>

