

ODV-3-843700-3R12-MN

Optidrive Eco VFD Datasheet

200 kW (300 HP), 370 A, 380-480 V, 3PH
IP20 Variable Frequency Drive with TFT Display



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	370 A
Supply Fuse or MCB (Type B)	500 A

Output Ratings

Motor Output Rating	200 kW (300 HP)
Output Voltage	0 – Supply Voltage
Output Current	370 A

Cable Information

Max Supply Cable Size	240 mm ² (0.37 sq in)
Max Motor Cable Size	240 mm ² (0.37 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	High Performance EMC Filter
Brake Transistor	No Brake Transistor
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard



Drive Dimensions

Size	8
Height	974 mm (38.35 in)
Width	444 mm (17.48 in)
Depth	423 mm (16.65 in)
Weight	124.5 kg (274.48 lbs)
Fixings	4 x M12

Packaged Dimensions

Height	660 mm (25.98 in)
Width	620 mm (24.41 in)
Depth	1020 mm (40.16 in)
Weight	144 kg (317.47 lbs)



Buy this drive or get more information:
<https://www.shc-gmbh.com>

